




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G02B 5/04</b>	<b>A1</b>	(11) International Publication Number: <b>WO 95/31738</b>
		(43) International Publication Date: 23 November 1995 (23.11.95)
<p>(21) International Application Number: PCT/US95/03973</p> <p>(22) International Filing Date: 24 April 1995 (24.04.95)</p> <p>(30) Priority Data: 08/242,264 13 May 1994 (13.05.94) US</p> <p>(71) Applicant: MINNESOTA MINING AND MANUFACTURING COMPANY [US/US]; P.O. Box 33427, Saint Paul, MN 55133-3427 (US).</p> <p>(72) Inventors: MILLER, Richard, A.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). AHO, Kenneth, A.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US). DREYER, John, F., Jr.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US).</p> <p>(74) Agents: BUCKINGHAM, Stephen, W. et al.; Office of Intellectual Property Counsel, Minnesota Mining and Manufacturing Company, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).</p>		<p>(81) Designated States: AU, CA, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report. With amended claims.</p>

(54) Title: DIRECTED REFLECTION OPTICAL DEVICE



## (57) Abstract

An optical device having a transparent body (11) and including two prism surfaces (16, 18) formed thereon. The composite structure exhibits two axis stability in that the angular relationship between the input beam (12) and the output beam (14) remains fixed for slight movement of the device (11) about two orthogonal axes.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## DIRECTED REFLECTION OPTICAL DEVICE

### Field of the Invention

5           The present invention is an optical device for redirecting incident light. More particularly, the invention relates to a structured optical sheet which redirects incident light through a fixed angle. This property is independent of the orientation of the plane of the sheet over a range.

### 10   Background

          Reflective structured optical sheets such as that taught by U.S. Patent 4,799,137 can be used to intercept and redirect incident light. In this reference the incident light is redirected through a design angle (ninety degrees) by refractive optical elements in combination with a reflective mirror coating. This is one example of a directed  
15   reflection optical device. The inclusion of a mirror in the composite structure requires vapor coating a metallic layer on the transparent plastic film or body portion of the device. Such metallic layers are optically inefficient, expensive to apply and can preferentially suffer environmental degradation.

          This type of device exhibits what may be called "single axis stability". The input  
20   light beam and the output bear a fixed angular relationship even when the device is rotated slightly about one axis. This property can be exploited in some applications.

### Summary

          The present invention includes two optically structured surfaces formed on  
25   opposite sides of a transparent body. This device exhibits what may be called "two axis stability". In operation, entry rays which approach the first or "upper" surface at a high angle of incidence are refracted into the body of the device by an array of prisms formed on the upper surface. These "captured" rays are directed by total internal reflection to the second or "lower" surface of the transparent material. The lower structured surface  
30   also includes an array of prisms which return the captured rays to the first or upper surface where they are again refracted toward the direction which is perpendicular to the

"initial" entrance ray. The two structured surfaces cooperate, capture and redirect a angle incident beam of light and redirect it through an angle, which in the illustrative example is ninety degrees. This process is to some degree, independent of the orientation of the optical device around two of three axes within limits. Thus the device exhibits "two axis stability".

#### Brief Description of the Drawings

The drawings show an illustrative example of the invention and throughout the figures identical reference numerals refer to identical structural elements, wherein:

FIG. 1 is a perspective view of the invention in its planar configuration;

FIG. 2 is a cross-section view of the invention;

FIG. 3 is a cross-section view of the invention; and

FIG. 4 is a perspective view of the invention in an arced configuration.

#### Detailed Description

The traditional corner cube reflector is referred to as retro-reflective because the reflected ray travels back along the same path as the incident ray. This property is preserved even when the corner cube is rotated within limits about all three axes. Thus the corner cube may be referred to as having "three axis stability". The corner cube should be compared with a plane mirror wherein the angle of incidence equals the angle of reflection. For this optical device the reflected ray follows the incident ray only when the angle is zero. In this narrow case the plane mirror is retro-reflective and since this property is preserved when the mirror is rotated about this single axis formed by the retro-reflected ray it may be said to have "single axis stability". The present invention described in detail below possesses two axis stability about the X and Y axis as seen in FIG. 1. In this sense it lies between the plane mirror and the corner cube device.

FIG. 1 is a perspective view of the optical device 10 in its planar configuration. In general, the body 11 is formed of transparent material and has a structured upper surface 16 and a structured lower surface 18. The upper surface 16 is an array of linear

prisms typified by prisms 24, 26 and 28. In operation, the central entrance ray 12 segment (ab) enters prism 24 on the first facet 23 of the prism 24 where it enters the body 11. Ultimately central exit ray 14 segment (fg) emerges from facet 30 of prism 26.

5       The vertical plane containing exit ray 14 is parallel to, but displaced from the vertical plane containing exit ray 12. In FIG. 1 the exit ray 14 will exit from the adjacent prism 26 as seen in the diagram. If the body thickness is increased sufficiently in the Z-direction, the exit ray will exit from the "next" or second adjacent prism 28. There is a necessary relationship between the geometry of the prisms and the thickness T of the  
10       body 11 which controls which prism delivers the exit ray. In general the efficiency of the optical device 10 is maximized by selecting a thickness which causes the exit ray to emerge from the adjacent prism 26.

FIG. 2 is a cross-section view of the optical device 10 cut along the Y axis. In this view a representative entrance ray 12 segment (ab) just grazes the peak of prism 36.  
15       This entrance ray 12 segment (ab) is refracted at the surface 23 of prism 24 at point (b) and ray segment (bc) undergoes total internal reflection at point (c) on the second surface 32 of prism 24. The ray (cd) then passes through the body 11 of the optical device 10 and is directed toward the linear prisms of the lower surface 18 where it is reflected as discussed in connection with FIG. 3.

20       For most common optical plastic materials having an index of refraction of between 1.45 to 1.6, and regular right prisms, the included acceptance angle for the optical device will equal approximately 13 degrees.

FIG. 3 is a cross-section view of the optical device 10 cut along the X axis. This view best illustrates reflection of ray segment (cd) the at the lower surface 18. The  
25       lower surface 18 includes an array of prisms including prism 40. The internal ray segment (cd) undergoes total internal reflection at point (d) on the first surface 42 of prism 40 and is directed through an angle of ninety degrees in the X-Z plane, directing it toward the second surface 44 of the prism 40. The second surface 44 of the prism 40 also reflects the ray (de) at point (e) through an angle of 90 degrees in the Y-Z plane,  
30       and returns it toward the upper surface 16. Entrance ray 13 and exit ray 15 illustrate

one axis of stability for the optical device 10 and they may be considered as though the device 10 was rotated slightly about the X axis as set forth in FIG. 1. In this illustration the segment (jk) is reflected and directed to point (l). Total internal reflection at (l) results in segment (jk) being parallel to segment (lm). However the difference in optical path between segments (hj) and (mn) result in ray 13 not being quite parallel to ray 15. However in contrast to a mirror lower surface the rays tend in the same direction.

The preceding description has described how an entrance ray enters a first prism and is turned through an angle of ninety degrees to form a displaced exit ray which leaves the optical device through a "different" prism. In this exemplary embodiment (example 1) the prism pitch for the upper surface P1 and the lower surface P2 is the same. That is, the distance between the peaks of the prisms, for both the upper surface and the lower surface are identical. In the exemplary embodiment (example 1) the prisms of the upper and lower surface have identical geometry and are regular right prisms where the first and second facets meet at an apex angle which is a right angle. Also in the exemplary embodiment, the prisms of the upper surface are orthogonal to the prisms of the lower surface. In tabular form the FIG.1 structure is set forth as follows:

20

## EXAMPLE 1

optical structure thickness	$T = .021$
upper surface (16) pitch (P1)	$P1 = P2 = .014$
upper surface prisms (36,26) are regular right prisms	
lower surface (18) pitch (P2)	$P2 = P1 = .014$
lower surface prisms (40) are regular right prisms	
P1 grooves are ninety degrees to P2 grooves	

25

Several variants of the invention are possible as well. For example the pitch P2 of the lower surface can be smaller than the pitch P1 of the upper surface, and the thickness T of the optical device 10 can be varied as well. It is also possible to vary the

30

prism angle of the upper surface to produce a structure which directs the exit ray to angles of less than ninety degrees or greater than ninety degrees. For example included angle of between 80 and 110 degrees may prove useful.

5           Although the present invention has thus far been described and shown in a planar configuration, it shall be understood that the device could also be formed and used in a curved or arced configuration such as that shown in FIG. 4. FIG. 4 shows the present device 10 curved along the Y axis in the positive Z direction. The device could also be curved along Y axis in the negative Z direction, or along X axis in the positive or  
10   negative Z direction. Compound curves could also be implemented. The device in any curved configuration maintains two axis stability about both the X and Y axis in the same manner as the planar configuration shown in FIGS. 1-3.

          The operation of the curved configuration shown in FIG. 4 is in all respects the same as that described above with respect to the planar configuration shown in FIGS. 1-  
15   3. Entrance ray 12 segment (ab) enters prism 24 on its first facet 23 where it enters the body 11. Ultimately exit ray 14 segment (fg) emerges from facet 30 of prism 26 in the same manner as described above with respect to the planar configuration shown in FIGS. 1-3.

          Although specific examples of the inventive structure have been described it is  
20   apparent that many modifications to the structure are possible without departing from the scope of the invention.

What is claimed is:

1. A reflective article comprising first and second structured  
5 surfaces, wherein:

said first structured surface includes a first array of prisms aligned  
in a first orientation;

- said second structured surface includes a second array of prisms  
aligned in a second orientation, wherein the second orientation is different from  
10 said first orientation;

such that a light ray incident on said first structured surface at an  
entrance angle is reflected at said second structured surface and exits from said  
first structured surface at an exit angle, the exit angle measured relative to said  
entrance angle.

15

2. The reflective article of Claim 7, wherein each prism in said first  
array of prisms includes a first facet and a second facet which intersect at a prism  
apex to define an apex angle.

- 20 3. The reflective article of Claim 8, wherein the apex angle of at  
least one of said prisms in said first array of prisms measures approximately 90  
degrees.

4. The reflective article of Claim 8, wherein the apex angle of at  
25 least one of said prisms in said first array of prisms measures between 80 and  
110 degrees.

5. The reflective article of Claim 7, wherein each prism in said  
second array of prisms includes a first facet and a second facet which intersect at  
30 the prism apex to define an apex angle.



6. The reflective article of Claim 11, wherein the apex angle of at least one of said prisms in said second array of prisms measures approximately  
5 90 degrees.

7. The reflective article of Claim 11, wherein the apex angle of at least one of said prisms in said second array of prisms measures between 80 and  
110 degrees.  
10

8. The reflective article of Claim 7, wherein said first orientation is approximately orthogonal to said second orientation.

9. The reflective article of Claim 7, wherein said entrance angle  
15 measures between 0 degrees and 13 degrees.

10. The reflective article of Claim 7, wherein said exit angle is approximately 90 degrees.

20 11. The reflective article of Claim 7 wherein a light ray incident on a first prism of said first structured surface at said entrance angle is reflected at said second structured surface and exits from a second prism of said first structured surface at said exit angle.

25 12. The reflective article of Claim 17, wherein said exit angle is approximately 90 degrees.

## AMENDED CLAIMS

[received by the International Bureau on 18 September 1995 (18.09.95);  
original claims 2-12 amended; remaining claims unchanged (2 pages)]

1. A reflective article comprising first and second structured surfaces,  
5 wherein:  
said first structured surface includes a first array of prisms aligned in a  
first orientation;  
said second structured surface includes a second array of prisms aligned  
in a second orientation, wherein the second orientation is different from said first  
10 orientation;  
such that a light ray incident on said first structured surface at an  
entrance angle is reflected at said second structured surface and exits from said first  
structured surface at an exit angle, the exit angle measured relative to said entrance  
angle.
- 15
2. The reflective article of Claim 1, wherein each prism in said first array  
of prisms includes a first facet and a second facet with intersect at a prism apex to  
define an apex angle.
- 20
3. The reflective article of Claim 2, wherein the apex angle of at least one  
of said prisms in said first array of prisms measures approximately 90 degrees.
4. The reflective article of Claim 2, wherein the apex angle of at least one  
of said prisms in said first array of prisms measures between 80 and 110 degrees.
- 25
5. The reflective article of Claim 1, wherein each prism in said second  
array of prisms includes a first facet and a second facet which intersect at the prism  
apex to define an apex angle.

6. The reflective article of Claim 5, wherein the apex angle of at least one of said prisms in said second array of prisms measures approximately 90 degrees.

5 7. The reflective article of Claim 5, wherein the apex angle of at least one of said prisms in said second array of prisms measures between 80 and 110 degrees.

8. The reflective article of Claim 1, wherein said first orientation is approximately orthogonal to said second orientation.

10

9. The reflective article of Claim 1, wherein said entrance angle measures between 0 degrees and 13 degrees.

10. The reflective article of Claim 1, wherein said exit angle is  
15 approximately 90 degrees.

11. The reflective article of Claim 1, wherein a light ray incident on a first prism of said first structured surface at said entrance angle is reflected at said second structured surface and exits from a second prism of said first structured surface at said  
20 exit angle.

12. The reflective article of Claim 11, wherein said exit angle is approximately 90 degrees.




Fig. 1






Fig. 4



## INTERNATIONAL SEARCH REPORT

Inter national Application No

PCT/US 95/03973

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 G02B5/04

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,4 883 341 (L.A.WHITEHEAD) 28 November 1989 see column 2; figure 3 ---	1
A	DE,A,19 22 780 (H.HILLESHEIM) 3 December 1970 see figures 1,4,5,8 ---	1
A	US,A,4 799 137 (K.A.AHO) 17 January 1989 cited in the application see abstract; figures 1-4 -----	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&amp;" document member of the same patent family

Date of the actual completion of the international search

23 June 1995

Date of mailing of the international search report

19.07.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Malic, K

## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 95/03973

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-4883341	28-11-89	CA-A- 1278203	27-12-90
DE-A-1922780	03-12-70	NONE	
US-A-4799137	17-01-89	AU-B- 596520	03-05-90
		AU-A- 1547688	02-11-88
		DE-D- 3851836	17-11-94
		DE-T- 3851836	27-04-95
		EP-A- 0357629	14-03-90
		JP-T- 2503250	04-10-90
		WO-A- 8807647	06-10-88
		US-A- 4874228	17-10-89

